# CHAR-MASTER Hamburger-Chicken-Wings-Steak Flame Broiler MODEL #7600 - 6 Burner - Flow-through - Single Chain - Bun Toaster

Designed for high volume operators for cooking delicious flame broiled hamburgers, chicken, wings and steak sandwiches. Infrared burners cook quickly and thoroughly, offering a better tasting product and sealed-in juices. Cooks up to 510 frozen, 4 oz. patties per hour.

### **FEATURES**

- Flow-through Operation
- Single Meat Chain
- 600 Degree F Operating Temperature
- Automatic Temperature Control
- Integrated Bun Toaster
- Heavy gauge stainless steel welded frame construction
- 6 Infrared burners for thorough cooking
- High Capacity
- 99% smoke-free with optional catalyst
- Easy Cleaning and Maintenance
- Single Pilot Ignition
- Side Burner Access Panel

### **BENEFITS**

- Consistency
- Versatility
- Speed
- Quality
- Flexibility
- Food Safety
- Labor Savings
- Gas/Energy Efficient

### **APPROVALS**

- UL Listed
- NSF/ANSI 4

### ADD-ON COMPONENTS

### **Extended Meat Chain**

Labor Savings

### **Extended Bun Chain**

Labor Savings

### Flat Table

Maximize storage space underneath

### **Tubular Stand**

Ease of cleaning

### **Catalytic Converter**

Eliminated 99% of smoke Reduces gas cost by over 25%

Helps "cool down" the kitchen

### **Catalyst Hood Kit**

Facilitates the installation of the Catalytic Converter in the field.

## **OPTIONAL PARTS**

### 220 Volt Female Receptacle

Necessary for use with a Bun Platen unit

### 48" Gas Hose

Eliminates gas leaks

### 3/4" Brass Quick Disconnect

Facilitates easy disconnect for cleaning

### **Cable Restraining Device**

Safety- relieves strain on gas hose

### **Emergency Spare Parts Kit**

Facilitates easy repairs, reducing down-time



# **CHAR-MASTER™** Universal Flame Broiler

MODEL 7600 Flow-through

DIMENSIONS	INCH	MM
Length	46	1168
Height	29-1/2	749
Width	37	940

WEIGHT	LB	KG
Shipping	650	294

EXHAUST	CFM	СМН
Typical	800	1360

ENERGY — GAS MODELS		
Gas connection 3/4" N.P.T.		
Electrical connection (specify exact voltage)		
Domestic	208-240Y120V IØ 50/60Hz 18A	
Export	200-240V IØ 50/60Hz 18A	
Natural Gas	3" W.C.	
BTU/hr	58,000	
kW	22.6	
Liquid Propane	8" W.C.	
BTU/hr	61,000	
kW	23.8	



750 Beta Drive, Unit "G" Cleveland, Ohio 44143 800-272-8546 440-460-3990

Fax: 440-460-3999

Email: info@BPSproductsinc.com

37" Overall Width (939.8 mm)



Height

27-1/2" Leg Width (698.5 mm)

46" Overall Length (1168 mm)



24-3/4" Leg Length (628 mm)

Metric dimensions rounded up to the neares whole millimieter. Specifications subject to change without notice.